

PS01 - REMOVE GROUT HAZE - LIGHT

Remove Light Grout Haze & Latex Film within 10 days of grouting

PRODUCT: [HAZE AWAY](#)



EQUIPMENT:

- [AQUABUG CLEANING KIT](#);
- Protective glasses & gloves;
- Scrub pads or brush;
- Broom
- Bucket & mop
- Clean water;
- Cotton towels;
- Optional: Wet vac;
- Optional: Low Speed Scrub machine

PRECAUTIONS:

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow contact with any non-recommended surface;
5. May slightly dull some polished calcium based surfaces e.g. marble, limestone, travertine, cement based terrazzo

PROCEDURE:


1. Sweep, vacuum, or wipe surface;
2. Dilute [HAZE AWAY](#) as follows with clean water:
 - a) LIGHT HAZE: Dilute 1 part [HAZE AWAY](#) to 3 parts clean water; (4 litres = 1 litre Haze Away to 3 litres water)
 - b) MODERATE HAZE: Dilute 1 part [HAZE AWAY](#) to 2 parts clean water; (4 litres = 1.30 litres Haze Away to 2.70 litres water)
 - c) HEAVY HAZE: Dilute 1 part [HAZE AWAY](#) to 1 part clean water or use neat. (4 litres = 2 litre Haze Away to 2 litres water)
3. Carefully apply solution to surface with a sponge or mop;
4. Allow minimum dwell time of 10 minutes. Longer dwell time may be required.
5. DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE - ADD MORE PRODUCT AS REQUIRED TO KEEP IT WET
6. Scrub with a white nylon pad or scrub machine;
7. Remove the dirty solution with a wet vac or mop;
8. Rinse thoroughly with clean water;
9. Repeat the process as necessary.

Note: Some areas may require longer dwell time and/or stronger solution.

PROCEDURE QUICK GUIDE:



Dilute depending on cleaning requirements




Apply diluted solution to the surface



After the appropriate dwell time, scrub surface



For Grout joints, scrub with a grout brush



Remove dirty solution with a wet vac then rinse



Surface is now clean and grout haze removed

Note A: Heavy grout haze or grout haze older than 10 days may require the use of [OXITREAT+](#)

Note B: Do not use [HAZE AWAY](#) on marble, limestone, travertine or on other acid-sensitive tile or stone.

Note C: Use [MICROSCRUB](#) to remove grout haze from polished natural stone & acid sensitive surfaces.

Note D: For high solids latex modified grouts mixing [OXITREAT+](#) and [STRIP-IT](#) may be required.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES