

# PS09 - Remove Heavy Porcelain Wax

Remove Heavy Porcelain Wax from Porcelain or Ceramic Tiles



## PRODUCT: XTREMECLEAN with MICROSCRUB

- EQUIPMENT:**
- AQUABUG CLEANING KIT;
  - Scrub pad or brush;
  - Broom
  - Bucket
  - Clean water;
  - Cotton towels.
  - Wet vac;
  - Optional: Scrub machine

- PRECAUTIONS:**
1. Read entire label, SDS & technical bulletin before using;
  2. Wear appropriate skin & eye protection;
  3. Use when surface temperature is between 4°C & 32°C;
  4. Do NOT allow contact with non recommended surfaces;
  5. Do NOT mix with other chemicals;
  6. Regular use of high alkaline cleaners will affect the performance of sealers, coatings & floor finishes;
  7. May lighten some dark grouts & affect some grout colourants.
  8. Do NOT use undiluted. The undiluted product can dull or discolour some surfaces;
  9. Do NOT allow product to dry on the surface. Add more product as required to keep wet.

- PROCEDURE:**
1. Sweep, vacuum, or wipe surface;
  2. Dilute XTREMECLEAN with clean water as follows depending on the severity of the problem:
    - a) **LIGHT:** Dilute 1 part XTREMECLEAN to 15 parts water.  
(1 litre = 70ml XtremeClean to 930 ml water)
    - b) **MODERATE:** Dilute 1 part XTREMECLEAN to 10 parts water  
(1 litre = 100ml XtremeClean to 900 ml water)
    - c) **HEAVY:** Dilute 1 part XTREMECLEAN to 5 part water ;  
(1 litre = 200ml XtremeClean to 800 ml water)
    - d) **STRIPPING:** Dilute 1 part XTREMECLEAN to 3 parts water;  
(1 litre = 330ml XtremeClean to 670 ml water)
  3. Carefully apply the solution to surface with a sponge or a mop;
  4. Allow minimum dwell time of 10 minutes. Longer dwell time may be required;
  5. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE - ADD MORE PRODUCT AS REQUIRED;**
  6. After the dwell time, add MICROSCRUB to standing solution then scrub with a white nylon pad, scrub brush or scrub machine;
  7. Remove the dirty solution with a wet vac or mop;
  8. Rinse thoroughly with clean water;
  9. Repeat the process as necessary.

**Note A:** For extreme heavy wax coatings, see use STRIP-IT as per label instructions

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

**READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES**