

# PS24 - Remove Smoke, Soot, Hydrocarbons, Red Soil

Remove Smoke, Soot, Hydrocarbons, Red Soil from Natural Stone, Porcelain Tiles, Pavers etc



**PRODUCT:** **BLAST HD™**

- EQUIPMENT:**
- AquaBug Cleaning Kit;
  - Clean water;
  - Scrub pad or brush;
  - Cotton towels.
  - Broom
  - Wet vac;
  - Bucket
  - Optional: Scrub machine

- PRECAUTIONS:**
1. Read entire label, SDS & technical bulletin before using;
  2. Wear appropriate skin & eye protection & use in a well ventilated area;
  3. Surface must be clean, dry & free from any sealers & coatings;
  4. Use when surface temperature is between 4°C & 32°C;
  5. Do NOT mix with other chemicals or allow contact with any non-recommended surfaces;
  6. Do NOT use on acid sensitive or polished surfaces;
  7. Do NOT mix in metal containers;
  8. Remove all metal jewellery before using;

- PROCEDURE:**
1. Sweep, vacuum, or wipe surface;
  2. If the surface is very porous, slightly pre-wet surface with water;
  3. Dilute **Blast HD™** as follows:
    - a) LIGHT: Mix 1 part product to 8 parts water;
    - b) MODERATE: Mix 1 part product to 5 parts water;
    - c) HEAVY: Mix 1 part product to 3 parts water;
    - d) EXTREME: Mix 1 part product to 1 part water or use neat;
  4. Carefully apply solution to surface with a sponge, roller or mop;
  5. Allow minimum dwell time of 10 minutes - up to 30 minutes
  6. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
  7. Scrub with a white nylon pad, scrub brush or scrub machine;
  8. Remove the dirty solution with a wet vac or mop;
  9. Rinse thoroughly with clean water;
  10. Repeat the process as necessary.

**Note 1:** Heavily soiled areas may require longer dwell time and/or stronger solution.

**Note 2:** Some stained surfaces may require resurfacing or replacing;

**Note A:** Do NOT use **Blast HD™** on polished marble, limestone, travertine or on other acid-sensitive tile or stone.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.

**READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST. KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES**