PS25 - Create Anti Slip on Slippery Tiles

Create a Slipe Resistant Surface on Porcelain, Tessellated & Ceramic Tiles

PRODUCT: **GRIP-IT T ™**

EQUIPMENT:

- AquaBug Cleaning Kit;
- Scrub pad or brush;
- Broom
- Bucket
- Clean water;
- Cotton towels.
- Wet vac;
- Optional: Scrub machine

PRECAUTIONS:

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin and eye protection;
3. Remove all metal jewellery before using;
4. Use in a well ventilated area or use an appropriate mask;
5. Use when surface temperature is between 4°C & 32°C;
6. Do NOT allow product to come in contact with any non-recommended surfaces;
7. Do NOT pour in metal buckets or containers;
8. Do NOT mix with ammoniated cleaners or any other chemicals;
9. Do NOT use on polished porcelain, acid sensitive or polished surfaces
10. Some dark coloured tiles can lighten in colour depending on how much micro-texture is created

PROCEDURE:

1. Sweep, vacuum or wipe for a clean, dry surface;
2. Pour Grip-It T™ into a suitable plastic paint tray, bucket or container;
3. Carefully apply Grip-It T™ evenly to surface with a suitable sponge, brush, natural bristle broom or mop;
4. DO NOT POUR DIRECTLY FROM BOTTLE TO THE SURFACE;
5. Allow to dwell for approx 5 minutes at a time -"dwell period";
6. After each 5 minute dwell period, test the amount of slip resistance created by using your shoe in a scuffing motion in the standing Grip-It T™ solution on the floor;
7. When desired level of slip resistance has been created, rinse off thoroughly with clean water;
8. DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE - ADD MORE PRODUCT AS REQUIRED TO KEEP IT WET;
9. Repeat the process as necessary.

NOTE: To reduce soiling & staining, seal with appropriate penetrating type sealer from Aqua-Seal STS™ - refer to our website www.aqua-seal.com.au;

SAFETY DIRECTIONS: **CORROSIVE**

1. Wear protective gloves, eye & skin protection when using.
2. Avoid breathing vapour or mist spray.
3. Avoid contact with skin & eyes.
4. May cause blindness & burns.
5. Burns might not be immediately painful or visible.
6. Obtain a supply of calcium gluconate gel
7. Wash tools, gloves & shoes thoroughly with clean water

Note A: Do NOT use Grip-It T™ on Polished Porcelain, Acid Sensitive or Polished Surfaces.
Note B: Grip-It T™ creates a slip resistant microtexture. Colour can be affected the more texture that is created.

This recommendation is intended as a general guideline. The actual procedure requirements, dilution ratios, dwell time etc may vary depending on type of surface, method of application and severity of the problem.
READ PRODUCT LABEL INSTRUCTIONS, TECHNICAL BULLETIN & SDS THOROUGHLY BEFORE USING. ALWAYS TEST FIRST.
KEEP SURFACE CLEAN AND DRY TO REDUCE THE POSSIBILITY OF SLIP & FALL ACCIDENTS AND INJURIES

AQUA-SEAL STONE+TILE SOLUTIONS
Aqua-Seal STS™ - Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am - 4.00pm
E: sales@aqua-seal.com.au www.aqua-seal.com.au
© Copyright July 2019