

# AQUA-SEAL GOLD+®

## Premium Natural Look Sealer for Stone, Terrazzo, Grout, Encaustic Tiles, Cement etc - NanoPlus + RapidSeal Formula



**DESCRIPTION:** AQUA-SEAL GOLD+® is a **PROFESSIONAL GRADE, PREMIUM, Low VOC (<5gm/L)**, natural look, no sheen, breathable, penetrating type sealer. **NANOPLUS** Formula penetrates deeper and chemically bonds to provide **MAXIMUM** stain resistance against oil, food, grease & grime plus help consolidate stone, reduce freeze/thaw damage, spalling and efflorescence. Built in **RAPIDSEAL** provides protection in 4 hours and **ACTIVESHIELD** Antimicrobial Action inhibits the growth of bacteria, mould and mildew. Non-Flammable, Non-Yellowing, Non-Coating, Water Based. UV and Chemical Resistant. Safe for food preparation areas.

**USE:** For all porous Natural Stone, Encaustic, Terrazzo and Porcelain tiles, Grout, Bricks, Saltillo, Terracotta, Concrete, Pavers etc in indoor, outdoor, domestic and commercial areas. Safe for food areas.

**TEST FIRST:** Always test first in an inconspicuous area to determine ease of application, coats required, colour stability & desired results. The end user must determine suitability of product for their own use.

### PRECAUTIONS & SAFETY DIRECTIONS:

1. Read entire label, SDS and technical bulletin before using;
2. Wear appropriate gloves, skin and eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Surface must be clean, dry and free from sealers and coatings;
5. Do NOT allow sealer to drip or leave drip marks on the surface;
6. Do NOT use on the underside of the tile or stone. If six sided/dip sealing is required, then use Ultra-Block;

**PREPARATION:** Use **XTREMECLEAN+** or **STONEWASH+** as per label to clean and prepare the surface.

**INSTRUCTIONS - PRE-SEALING:** For quick and easy clean-up after grouting as porous surface may stain during install and grouting.

1. Pre-seal surface before installing or 24 hours after installation
2. Do NOT saturate the open grout joints;
3. Allow minimum 24 hours cure time before grouting;
4. If using dark or contrasting grout, apply **GROUT RELEASE PRO** after **AQUA-SEAL GOLD+®** has cured, then grout as usual.

### INSTRUCTIONS - SEALING:

1. Apply sealer to clean, dry surface using a sealer applicator, pump sprayer, sealer sponge, brush, paint roller or paint pad;
2. Ensure even coat and coverage then work product in thoroughly;
3. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE - ADD MORE TO KEEP IT WET FOR 5-10 MINUTE PERIOD;**
4. After 5-10 minutes, wipe the surface **COMPLETELY DRY** with absorbent paper or cotton towels to remove any excess;
5. Repeat this process for each application;

### APPLICATION NOTES:

1. For vertical surfaces apply bottom to top and avoid run-down;
2. Porous surfaces will require additional coats. If 2 or more coats are required, allow minimum 30 minutes between coats;
3. 2 hours after final coat, do a test to determine if surface is properly sealed. Apply some water droplets. If water is easily absorbed then apply an additional coat. Wait 2 hours and repeat the test.
4. The surface is ready for light traffic after 2 hours. Keep dry for minimum 24 hours. Full cure in 24 hours.


### QUICK GUIDE FOR SEALING:



1. Pour into a suitable sized container



2. Apply sealer to the surface and work it in



3. After 5-10 minutes wipe surface completely dry

**LIMITATIONS:** NOT a waterproofing agent and will NOT prevent surface wear, scuff marks or etching from harsh or acidic products. Spills should be wiped up immediately to help minimise staining.

**EXPECTED WEAR:** Will vary depending on surface texture and hardness, traffic wear plus frequency and type of cleaning products used. Harsh cleaning including pressure washing, high alkaline, acidic or solvent-based cleaners and/or weather exposure will affect wear and performance. High traffic and exterior areas will require more frequent re-application. **RE-SEAL AS NECESSARY.**

**COVERAGE:** Approximately 40-160m<sup>2</sup> per 4 litre per coat. (Minimum 2 coats suggested). It will vary depending on the density, porosity, texture and absorption. Also weather conditions, the application method and number of coats required. See table below as a guide (per 4L per coat). Full coverage chart at [www.sealersplus.com.au](http://www.sealersplus.com.au)

• Bluestone Flamed	60-80 m <sup>2</sup>	• Porcelain Tiles	120-160 m <sup>2</sup>
• Encaustic Tiles	60-80 m <sup>2</sup>	• Terrazzo Polished	100-120 m <sup>2</sup>
• Marble Honed	60-80 m <sup>2</sup>	• Travertine Honed	80-100 m <sup>2</sup>

### MAINTENANCE:

- **EZYCLEAN+** for routine, everyday cleaning plus disinfecting;
- **XTREMECLEAN+** for periodic heavy duty cleaning & disinfecting;
- **STONE WASH+** for cleaning, conditioning & disinfecting of stone;
- **STONE GEL+** for cleaning and disinfecting vertical surfaces;
- **BOOST'N'CLEAN+** for routine cleaning and re-sealing;
- **REFRESH+** for cleaning and disinfecting food surface areas;

**HANDLING, STORAGE & CLEAN UP:** Close container tightly after each use; Store in original container between 4°C & 32°C. Shelf life is approx 3 years in unopened container - less after opening; Storage beyond that time does not necessarily mean the product is not usable. Do a small test area first; Do not re-use container. Discard in rubbish; Clean tools and clothing with water before they dry.

**FIRST AID:** Contact a doctor or Poisons Information Centre (Aust 131-126, NZ 0800 764 766). First aid not generally required. Do NOT induce vomiting. Wash mouth with water. If in eyes flush with clean, running warm water for at least 5 minutes. Rinse any skin contact.

**PRODUCT WARRANTY - SEALERS PLUS** (An Aqua-Seal Brand) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**



**SEALERS PLUS** (AN AQUA-SEAL BRAND)

P: +61 2 9521 4000 Mon - Fri 9.00am-4.00pm E: [sales@sealersplus.com.au](mailto:sales@sealersplus.com.au)

AUS: [www.sealersplus.com.au](http://www.sealersplus.com.au) NZ: [www.sealersplus.co.nz](http://www.sealersplus.co.nz) Global: [www.sealersplus.com](http://www.sealersplus.com)



© Copyright July 2022