# Aqua-Seal Gold+

## Premium Natural Look Penetrating Sealer – NanoPlus™ Formula

+ Natural Look, No Sheen – Breathable Penetrating Sealer
+ Our Highest Level of Stain Resistance – Water, Oil, Grease, Food & Grime
+ Stain Protection in 4 Hours – Full Cure in 24 Hours
+ Low VOC, Water Based, Non-Flammable, Non-Yellowing & UV Resistant
+ Also a Pre-Grouting Sealer for Quick, Easy Grout Clean-Up

Product page, SDS & more

## DESCRIPTION

**Aqua-Seal Gold+** is a **Professional Grade**, low VOC, natural look, no sheen, breathable, penetrating sealer. Using advanced short-chain C6 technology, it delivers our highest level of stain resistance – the premium tier of the Aqua-Seal sealer range – helping resist water, oil, grease, food and grime. Water based, non-flammable, non-yellowing and UV resistant. Built-in RapidPlus™ gives stain protection in 4 hours. Also use as a pre-grouting sealer.

## WHAT DOES IT DO

The NanoPlus™ sealing molecules penetrate into the surface and line the pore walls, reducing porosity. Spills sit on the surface so they can be wiped up before they stain. It also helps reduce water absorption, which can contribute to efflorescence, mould and mildew problems.

## SUITABLE FOR

All porous surfaces: natural stone, terrazzo, encaustic and porous porcelain tiles, grout, bricks, Saltillo, terracotta, concrete and pavers. Suitable for food preparation surfaces once fully cured, e.g. bench-tops, table-tops and bar-tops. **Not for** glazed or non-porous tiles, or surfaces with an existing sealer or coating.

### Surfaces

+ Basalt & Bluestone
+ Granite & Quartzite
+ Marble & Limestone
+ Travertine & Sandstone
+ Slate
+ Terrazzo & Encaustic
+ Porous Porcelain
+ Grout
+ Brick, Saltillo & Terracotta
+ Concrete & Pavers

### Where

+ Floors & Walls
+ Bench-tops & Vanities
+ Table & Coffee Tables
+ Bathrooms & Kitchens
+ Patios & Pool Surrounds
+ Driveways & Walkways
+ Facades
+ Indoor & Outdoor

## WHERE TO USE

Domestic and commercial, indoor and outdoor: homes, hotels, airports, retail, kitchens and restaurants.

## TEST FIRST

Always test first in an inconspicuous area to check coats needed and colour. End user must determine suitability of product for their own use.

## WHAT YOU NEED BEFORE YOU START

- Protective gloves, eye, skin and foot protection;
- **XtremeClean+** or **Stone Wash+** to clean and prepare the surface;
- Sealer applicator, pump sprayer, sealer sponge, brush, roller or paint pad, and a plastic container or tray;
- Plenty of paper towels or clean, absorbent cotton cloths.

## PREPARATION

Surface must be clean, dry and free from other sealers and coatings. Use **XtremeClean+** or **Stone Wash+** as per label, rinse and allow to dry.

## HOW TO USE – SEALING

1. Apply to a clean, dry surface with a sealer applicator, pump sprayer, sponge, brush, roller or pad;
2. Ensure an even coat and coverage, then work the sealer in thoroughly;
3. **DON'T ALLOW PRODUCT TO DRY ON SURFACE – ADD MORE SEALER TO KEEP IT WET FOR 10 – 15 MINUTES**;
4. After 10 – 15 minutes, wipe the surface **COMPLETELY DRY** with absorbent paper or cotton towels;
5. Repeat for each coat. Minimum 2 coats; porous surfaces may need more. Vertical surfaces: work bottom to top.


Pour into a suitable container


Apply and work it into the surface


After 10 – 15 min wipe **completely** dry

**Watch: Aqua-Seal Gold+ Natural Stone, Tile & Grout Sealer**
Scan to watch the Aqua-Seal Gold+ video
youtu.be/QmDIAXZdjNo

## HOW TO USE – PRE-SEALING

1. Pre-seal before installing, or 24 hours after installation. Do NOT saturate open grout joints;
2. Allow minimum 24 hours cure before grouting;
3. Dark or contrasting grout, or rough porous surfaces: apply **Grout Release+** after **Aqua-Seal Gold+** has cured;
4. **Tip:** add **Haze Away** to the final rinse water when grouting to help prevent grout haze.

## DRYING & CURING (20°C)

| | |
|---|---|
| Between coats | **Min. 30 minutes** |
| Water test | **2 hours after final coat** |
| Light foot traffic | **After 2 hours** |
| Stain protection | **From 4 hours** |
| Keep dry / full cure | **24 hours** |

## THE WATER DROP TEST

2 hours after the final coat, sprinkle a few drops of water. If it soaks in easily, apply another coat, wait 2 hours and test again. If it beads, the surface is sealed.

**SEALERS PLUS** (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
**Aust:** sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026

# Aqua-Seal Gold+

**Premium Natural Look Penetrating Sealer – NanoPlus™ Formula**

## PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS and technical bulletin before using;
2. Wear appropriate gloves, skin, eye and foot protection;
3. Use when surface temperature is between 4°C and 32°C;
4. Surface must be clean, dry and free from other sealers and coatings;
5. Do NOT allow sealer to drip or leave drip marks;
6. Do NOT use on the underside of the tile or stone. For six-sided / dip sealing use **Condense Plus** or **Ultra-Block** first.

## APPROXIMATE COVERAGE

| Surface | Coats | m² per Litre (per coat) | m² per 4 L Bottle (per coat) |
|---|---|---|---|
| Bluestone Flamed | 2+ | 15 – 20 | **60 – 80** |
| Encaustic Tiles | 2+ | 8 – 10 | **32 – 40** |
| Granite Honed | 2+ | 15 – 20 | **60 – 80** |
| Marble Honed | 2+ | 15 – 20 | **60 – 80** |
| Limestone Honed | 2+ | 10 – 15 | **40 – 60** |
| Sandstone Honed | 2+ | 8 – 10 | **32 – 40** |
| Saltillo | 3 – 5 | 2 – 4 | **8 – 16** |
| Terracotta-Pressed | 2+ | 10 – 15 | **40 – 60** |
| Terrazzo Honed | 2+ | 15 – 20 | **60 – 80** |
| Travertine Honed | 2+ | 15 – 20 | **60 – 80** |
| Concrete & Pavers | 2+ | 10 – 15 | **40 – 60** |
| Engineered Stone & Tessellated | 2+ | 15 – 20 | **60 – 80** |
| Slate | 2+ | 15 – 20 | **60 – 80** |
| Porcelain Polished (Porous) | 2+ | 30 – 40 | **120 – 160** |
| Mother of Pearl | 2+ | 30 – 40 | **120 – 160** |

Coverage is **approximate only**: approx. 2 – 40 m² per litre per coat, minimum 2 coats (Saltillo 3 – 5 coats). It depends on the density, porosity, texture and absorption of the surface, the weather, the application method and the number of coats. Use the Sealer Calculator for your job.

### How much do I need? – Sealer Calculator

Pick your surface, finish and area and our free calculator works out how much **Aqua-Seal Gold+** you need for the recommended coats, which pack sizes to buy and the approximate cost. Also in our Product Selector · video: youtu.be/vo_xtDzqE6M

## TECHNICAL DATA

| | |
|---|---|
| **Product type** | Water-based NanoPlus™ short-chain C6 penetrating sealer |
| **Finish** | Natural look, no sheen |
| **Appearance** | Clear, straw/amber liquid |
| **pH** | approx. 8 |
| **VOC** | Low VOC: 5 g/L – within the Green Star VOC limit for sealers |
| **Application** | 4°C – 32°C; min. 30 min between coats |
| **Shelf life** | Approx. 3 years unopened |
| **Pack sizes** | 250 mL · 1 Litre · 4 Litre · 15 Litre · 20 Litre |
| **Transport** | Not a Dangerous Good |
| **SDS** | sealersplus.com.au/sds/Aqua-Seal-Gold-SDS.pdf |

## CAUTION

Not classified as hazardous (Safe Work Australia GHS 7). Not a Dangerous Good. Keep out of reach of children. Avoid contact with eyes and skin.

## LIMITATIONS

- A penetrating sealer, not a membrane, and will NOT prevent surface wear, scuff marks or etching from harsh or acidic products. Not a substitute for a compliant damp-proof membrane, drainage or correct substrate preparation;
- Wipe up spills immediately to help minimise staining;
- Other looks: for a non-gloss colour enhanced look use **Enhance'N'Seal**; for a gloss finish use **Gloss'N'Seal**.

## EXPECTED WEAR & MAINTENANCE

Wear depends on surface texture and hardness, traffic and the cleaning products used. Pressure washing, high alkaline, acidic or solvent cleaners and weather exposure all affect wear; high traffic and exterior areas need more frequent re-application. Do the water drop test regularly and **re-seal as necessary**.

+ **EzyClean+** – everyday / weekly rinse-free cleaning & disinfecting;
+ **Boost Plus** – everyday / weekly cleaning & re-sealing;
+ **AquaGuard** – spray & wipe cleaning & re-sealing (bench-tops);
+ **ReFresh+** – daily food-prep surface cleaning & disinfecting;
+ **XtremeClean+** – heavy duty monthly / quarterly cleaning;
+ **Stone Wash+** – monthly / quarterly cleaning & conditioning;
+ **Stone Gel+** – cleaning vertical surfaces;

## HANDLING, STORAGE & CLEAN UP

- Close container tightly after use. Store in the original container between 4°C and 32°C;
- Shelf life approx. 3 years unopened – less after opening. Do a small test area first if stored longer;
- Clean tools and clothing with water. Do not re-use container. Discard in rubbish.

## FIRST AID

Contact a doctor or Poisons Information Centre (Australia Ph: 131 126, NZ Ph: 0800 764 766). First aid not generally required. Do NOT induce vomiting. Wash mouth with water. **Eyes:** Flush with clean, running warm water for at least 5 minutes. **Skin:** Rinse with clean running water.

## ABOUT OUR FLUOROPOLYMER TECHNOLOGY

Modern short-chain C6 fluoropolymer chemistry: does not contain PFOS, PFOA or PFHxS (the long-chain substances restricted under IChEMS).

## MADE IN AUSTRALIA

**PRODUCT WARRANTY – SEALERS PLUS** (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**



© October 2026