Colour'N'Seal

Premium Grout Colourant to Renew, Re-Colour & Seal Grout

+ Re-Colour, Renew & Seal Existing Grout in One Step
+ NanoPlus™ Water Based Modified Epoxy Formula
+ Helps Resist Stains from Oil, Food, Grease & Grime
+ Even, New-Look Grout Joints – 25 Colours
+ Walls & Floors, Indoor & Outdoor

Product page, SDS & more

DESCRIPTION

Colour'N'Seal is a **Professional Grade**, one-part premium grout colourant using a NanoPlus™ water based modified epoxy formula to re-colour, renew, revive and seal existing grout. It gives an even coloured, new-look grout joint and helps resist stains from oil, food, grease and grime.

WHAT DOES IT DO

The coloured, sealing film is worked into the grout joint, where it covers stains and uneven colour and seals the grout surface, so spills sit on top and are easier to wipe up.

SUITABLE FOR

Textured, sanded, un-sanded and most epoxy grout on walls and floors, in domestic and commercial, indoor and outdoor areas. **Not for** areas that are submerged, hold pooling water or stay wet. Take extra care around textured or porous tiles and stone.

TEST FIRST

Always test first in an inconspicuous area to check ease of application and clean-up, number of coats, colour and the desired result. End user must determine suitability of product for their own use.

WHAT YOU NEED BEFORE YOU START

- Gloves and eye protection;
- **OxiTreat+** (smooth grout, to create texture) or **XtremeClean+** (textured grout) to prepare the joint;
- A **Colour'N'Seal Applicator** brush or a kid-sized toothbrush;
- A slightly damp chamois, cloth or paper towels; a moisture meter for showers.

PREPARATION

Prepare the grout with **OxiTreat+** (smooth grout, to create texture) or **XtremeClean+** (existing textured grout). Rinse thoroughly, then allow to dry **COMPLETELY**. Grout must be textured, clean, completely dry, free from any sealers, coatings and cleaner residue, and sit lower than the tile. Strip existing colourant or prepare epoxy grout with **Strip-It**.

HOW TO USE

1. **SHAKE WELL BEFORE USING**;
2. Apply a small amount of product directly onto the grout;
3. Work it along the joint in a scrubbing motion with the applicator brush or toothbrush – a thin, even coat; limit product on the tile surface for easier clean up;
4. Immediately wipe excess off the tile with a slightly damp chamois, cloth or paper towel;
5. **DO NOT ALLOW TO DRY ON TILES FOR MORE THAN 30 MINUTES** – clean-up becomes difficult;
6. Contrasting colours may need a 2nd coat – allow 2 hours between coats. Two thin coats give the best sealing performance.

Dried on tiles? Spray a fine mist of water, leave 3 – 5 minutes, then scrub with a white pad (or a bristle brush on textured surfaces) **ACROSS** the grout joint – do not scrub in the joint.

Watch: How to Re-colour & Seal Grout: Full Colour'N'Seal How-To
Scan to watch the full Colour'N'Seal how-to
youtu.be/_49K4UttVLA

TIPS FOR AN EVEN COLOUR

+ Using more than one bottle of a colour? Mix them all together in a large container first and check batch numbers;
+ Showers: use a moisture meter to confirm the grout is COMPLETELY dry before applying;
+ Grout flush with or above the tile wears faster – rake it back below the tile surface first.

DRYING & CURING (20°C)

Between coats	**2 hours**
Light traffic	**After 2 hours**
Keep dry	**Min. 24 hours**
Full cure	**24 – 48 hours**
Shower floors & wet areas	**Min. 48 hours**

EXPECTED WEAR & MAINTENANCE

Wear depends on traffic and the frequency and type of cleaning products used. Harsh cleaning methods, pressure washing, high alkaline, acidic or solvent-based cleaners and weather exposure all affect wear. Showers, high traffic and exterior areas need more frequent re-application. **RE-APPLY AS NECESSARY**.

+ **EzyClean+** – rinse-free, pH-neutral everyday cleaning & disinfecting;
+ **XtremeClean+** – periodic heavy duty cleaning;
+ **Grout Clean+** – spray-on heavy duty grout cleaning.

SEALERS PLUS (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
Aust: sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026

Colour'N'Seal

Premium Grout Colourant to Renew, Re-Colour & Seal Grout

PRECAUTIONS & SAFETY DIRECTIONS

1. Read label, SDS and technical bulletin before using;
2. Wear gloves and eye protection;
3. Ensure existing grout sits lower than the tile;
4. Grout must be textured, clean, COMPLETELY dry and free from any sealers and coatings;
5. Use when surface temperature is between 4°C and 28°C;
6. Textured or porous tile and stone surfaces need more care – check for staining and ease of clean-up first;
7. Do not use acid or solvent based cleaners on the coloured grout.

APPROXIMATE COVERAGE

Tile size (3 mm grout joint)	m² per 250 mL Bottle (per coat)
200 × 200 mm	**approx. 20**
300 × 300 mm	**approx. 30**
400 × 400 mm	**approx. 40**
600 × 600 mm	**approx. 60**

Coverage is **approximate only**. It depends on grout porosity, joint width and depth, the application method and the number of coats.

TECHNICAL DATA

Product type	One-part NanoPlus™ water based modified epoxy grout colourant
Appearance	Pigmented opaque liquid, slight odour
pH	approx. 8.2
Application	4°C – 28°C; 2 hours between coats
Shelf life	Approx. 3 years unopened
Pack size	250 mL · 25 colours
Transport	Not a Dangerous Good
SDS	sealersplus.com.au/sds/Colour-N-Seal-SDS.pdf

COLOURS (250 ML)

Ultra White · White · Linen White · Antique White · Alabaster · Vanilla · Buff · Canvas · Travertine · Mocha · Havana · Olive · Macchiato · Cocoa · Misty Grey · Silver Fox · Light Grey · Silver · Magellan Grey · Grey · Slate Grey · Gunmetal Grey · Charred Ash · Midnight · Black

Colour swatches on marketing material are indicative only and can vary with printing and screen resolution. Shade variation can occur with batch, job site, lighting and surrounding conditions.

CAUTION

Not classified as hazardous (Safe Work Australia GHS). Not a Dangerous Good. Keep out of reach of children. Avoid contact with eyes and skin. Wash skin after contact.

LIMITATIONS

- A grout colour sealer, not a membrane. Not a substitute for a compliant damp-proof membrane, drainage or correct substrate preparation;
- Do not use under water, in pooling water or in areas that stay wet. Shower floors need good falls so water runs off;
- Cracked grout lets moisture in – re-grout before colouring;
- Wipe up spills immediately to help minimise staining.

HANDLING, STORAGE & CLEAN UP

- Close container tightly after each use. Store between 4°C and 32°C;
- Shelf life approx. 3 years unopened. Storage beyond that time does not mean it is unusable – do a small test area first;
- Clean tools and clothes with water before the product dries. Do not re-use container. Discard in rubbish.

FIRST AID

Contact a Poisons Information Centre (Australia Ph: 13 11 26, NZ Ph: 0800 764 766) or a doctor. **Ingestion:** do NOT induce vomiting; wash mouth with water and give some water to drink. **Eyes:** flush with clean running water. **Skin:** wash with plenty of water; seek medical advice if irritation develops.

RELATED PRODUCTS

+ **OxiTreat+** – prepare smooth grout;
+ **Strip-It** – strip old colourant;
+ **Grout Clean+** – heavy duty grout cleaning;
+ **EzyClean+** – everyday care.

MADE IN AUSTRALIA

PRODUCT WARRANTY – SEALERS PLUS (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**

SEALERS PLUS (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
Aust: sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026