# Grip-It T

## Heavy Duty Anti-Slip Treatment for Ceramic, Porcelain & Tessellated Tiles

+ Helps Reduce Slip Risk on Wet, Slippery Tiles
+ Creates a Long-Lasting Micro-Texture in the Tile Glaze
+ NOT a Sealer or Coating – Nothing to Peel or Go Yellow
+ Glazed & Unglazed Ceramic, Porcelain & Tessellated Tiles

Product page, SDS & more

## DESCRIPTION

**Grip-It T** for Tiles is a **Professional Grade** anti-slip treatment that creates a long-lasting, slip resistant micro-texture on the surface of the tile. It is NOT a sealer or a coating, so there is nothing to peel or go yellow. Helps make wet, slippery tiled areas less slippery.

## WHAT DOES IT DO

It works by micro-etching the glaze of the tile. The longer it is allowed to dwell on the surface, the more micro-texture it creates and the more slip resistance is achieved, so you control the result by testing as you go.

## SUITABLE FOR

Glazed and unglazed ceramic, porcelain and tessellated tiles in domestic and commercial, indoor and outdoor areas, including polished tiles (test first: the polish will be reduced, see Precautions). **Not** for natural stone or acid-sensitive surfaces.

**Where**
+ Bathrooms & Showers
+ Kitchens & Laundries
+ Pool Areas
+ Balconies & Patios
+ Entrances & Corridors
+ Living Areas

**Commercial**
+ Supermarkets & Retail
+ Airports & Foyers
+ Hotels
+ Restaurants & Bars
+ Commercial Kitchens
+ Aged Care

## TEST FIRST

Always test first in an inconspicuous area or on a spare tile to determine ease of application, the dwell time needed for the slip resistance you want, colour and surface look stability and overall results. User must determine suitability for their use.

## WHAT YOU NEED BEFORE YOU START

1. Chemical resistant gloves, eye / face protection, protective clothing, boots and a watch for timing;
2. **XtremeClean+** or **Stone Wash+** to clean & prepare the surface;
3. PLASTIC buckets or paint tray plus a clean sponge, roller or mop to apply (no metal);
4. Hose or separate bucket & mop plus plenty of clean water for rinsing;
5. TIP: a wet vac to help remove **Grip-It T** from the tiles before rinsing.

## SURFACE PREPARATION

Use **XtremeClean+** or **Stone Wash+** as per label instructions to ensure a clean, dry surface before starting.

## HOW TO USE

1. Sweep, vacuum or wipe tiles for a clean, dry surface;
2. Pour **Grip-It T** into a PLASTIC paint tray, bucket or container. DO NOT POUR DIRECTLY FROM THE BOTTLE ONTO THE SURFACE;
3. Carefully apply **Grip-It T** evenly to the tile surface with a clean sponge, roller or mop – DO NOT SPRAY;
4. Allow to dwell initially for about 5 minutes (the “dwell period”);
5. After 5 minutes, test the slip resistance with your shoe or a gloved hand in a scuffing / rubbing motion in the standing solution, keeping track of the dwell time;
6. If more slip resistance is needed, leave it longer and test again every 5 minutes until you achieve the desired result;
7. **DON’T ALLOW PRODUCT TO DRY ON SURFACE – ADD MORE PRODUCT TO KEEP WET AND ACTIVE**;
8. When you are happy with the result, remove **Grip-It T** with a wet vac and rinse thoroughly with clean water;
9. Repeat the process as necessary to achieve your desired slip resistance.

## CONDITIONS

Use when surface temperature is between 4°C and 28°C. Keep the area well ventilated.

## WATCH HOW TO USE

**Watch: Anti-Slip Tile Treatment: Grip-It T for Tiles**
Scan to watch the Grip-It T how-to video
youtu.be/FwfDy1KAxNA

## PRECAUTIONS

1. Read entire label, SDS and technical bulletin before using;
2. Do NOT allow contact with acid-sensitive or non-recommended surfaces (natural stone, glass, metal, chrome, enamel);
3. Do not pour into metal containers or mix with other chemicals;
4. May affect dark tiles, dark grouts, metal and polished surfaces. Depending on how much micro-texture is created, some dark tiles can lighten in colour and polished porcelain will lose its polish (polished to satin to matt);
5. Remove metal jewellery before use – corrosive to metals;
6. Obtain calcium gluconate gel before starting, in case product gets on skin;
7. **WASH UNDERSIDE OF SHOES BEFORE STEPPING ONTO OTHER AREAS.**



© October 2026

# Grip-It T

## Heavy Duty Anti-Slip Treatment for Ceramic, Porcelain & Tessellated Tiles

### APPROXIMATE COVERAGE

| Application | m² per Litre | m² per 4 L Bottle |
|---|---|---|
| One application (as supplied) | 10 – 15 | **40 – 60** |

Coverage is **approximate only** and depends on the slip resistance required, the tile texture and how many times the process needs to be repeated (about 100 mL per m²). Use the Product Selector calculator for your job.

### TECHNICAL DATA

| | |
|---|---|
| **Product type** | Ready to use acidic anti-slip treatment (micro-etch) for tiles |
| **Active** | Ammonium bifluoride 15 g/L |
| **Appearance** | Clear, colourless liquid, no odour |
| **Dilution** | None – use as supplied |
| **Dwell time** | Approx. 5 minutes, then test every 5 minutes |
| **Application temp.** | 4°C – 28°C surface temperature |
| **Shelf life** | Approx. 3 years unopened – less after opening |
| **Pack sizes** | 1 Litre · 4 Litre (Australia only) |
| **Transport** | Dangerous Good: UN3264, Class 8, PG III |
| **SDS** | sealersplus.com.au/sds/Grip-It-T-SDS.pdf |

### ONGOING MAINTENANCE

After treating the surface, these products help keep the slip resistance properly maintained:

+ **EzyClean+** – routine daily / weekly cleaning;
+ **XtremeClean+** – periodic heavy duty cleaning;
+ **Aqua-Seal Gold+** – seal the treated surface to help reduce soiling and staining and make ongoing cleaning easier.

### HANDLING, STORAGE & CLEAN UP

- Keep only in the original container. Close tightly after each use and keep upright. Store locked up in a well ventilated cool area, protected from sunlight;
- Shelf life approx. 3 years unopened – less after opening. Storage beyond that time does not necessarily mean the product is not usable;
- Do not re-use container. Rinse and discard in rubbish. Wash tools, gloves and boots with water before they dry.

## DANGER

**UN3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.** (ammonium bifluoride) Class 8, PG III. Hazardous according to Safe Work Australia (GHS 7). **H290** May be corrosive to metals. **H301** Toxic if swallowed. **H311** Toxic in contact with skin. **H314** Causes severe skin burns and eye damage. **H332** Harmful if inhaled. **H402** Harmful to aquatic life. Do not breathe fumes, mists, vapours or spray. Wear protective gloves, clothing, boots and eye or face protection. Do NOT kneel in product. Do not eat, drink or smoke when using. Store locked up. Keep out of reach of children.

### FIRST AID

Immediately contact Poisons Information Centre (Australia Ph: 131 126, NZ Ph: 0800 764 766) or a doctor. **Ingestion:** Do NOT induce vomiting. Immediately rinse mouth with water and call a Poisons Centre or doctor. **Eyes:** Immediately flush with clean running water for at least 15 minutes, removing contact lenses if easy to do, and see a doctor. **Skin & hair:** Remove contaminated clothing immediately. Flush skin and hair under running water for 15 minutes, then apply calcium gluconate gel and seek medical attention. Symptoms of burns may be delayed. **Inhalation:** Remove to fresh air and keep at rest. Seek medical advice. **General:** If irritation persists or you feel unwell, seek medical attention.

### LIMITATIONS

- For ceramic, porcelain and tessellated tiles only (including polished) – not natural stone or acid-sensitive surfaces;
- Slip resistance achieved depends on the tile, dwell time and number of applications. Test and measure on site where a specific slip rating is required;
- Will reduce the polish on polished tiles (polished to satin to matt).

### MADE IN AUSTRALIA

**PRODUCT WARRANTY – SEALERS PLUS** (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**

**SEALERS PLUS** (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
**Aust:** sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026