

Haze Away™

Grout Haze - Removal & Prevention



DESCRIPTION & USE

Haze Away™ is a non acidic problem solver formulated to simplify the grout clean up process by helping to prevent grout haze from cement based, latex modified & epoxy grout. Helps prevent latex film from forming on stone & tile surfaces. Can also be used to remove existing grout haze & latex film within 10 days of grouting. **USE:** For encaustic tiles, ceramic tiles, porcelain tiles, tessellated tiles, natural stone.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection;
3. Use when surface temperature is between 4°C & 32°C;
4. Do not allow contact with any non-recommended surface;
5. May slightly dull some polished calcium based surfaces e.g. marble, limestone, travertine, cement based terrazzo

INSTRUCTIONS:

TO PREVENT GROUT HAZE & LATEX FILM:

1. Mix grout & apply to grout joints as per manufacturers instructions;
2. During **FINAL** grout clean up process, mix 100ml of **Haze Away™** with 4 litres of clean water;
3. Continue grout clean up process - wring off excess solution from grout sponge ensuring a damp sponge action;
4. Wipe diagonally across the tiles;
5. Change solution as it gets dirty & loses effectiveness;
6. Remove & rinse off the cleaning solution with a slightly damp clean grout sponge or cotton towel using only clean water.

TO REMOVE GROUT HAZE & LATEX FILM WITHIN 10 DAYS OF GROUTING:

1. Sweep, vacuum, or wipe surface;
2. Dilute Haze Away™ as follows with clean water:
 - a) **LIGHT HAZE:** Dilute 1 part Haze Away™ to 3 parts clean water;
 - b) **MODERATE HAZE:** Dilute 1 part Haze Away™ to 2 parts clean water;
 - c) **HEAVY HAZE:** Dilute 1 part Haze Away™ to 1 part clean water or use neat.
3. Carefully apply solution to surface with a sponge or mop;
4. Allow minimum dwell time of 10 minutes. Longer dwell time may be required.
5. **DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE;**
6. Scrub with a white nylon pad or scrub machine;
7. Remove the dirty solution with a wet vac or mop;
8. Rinse thoroughly with clean water;
9. Repeat the process as necessary.

Note: Some areas may require longer dwell time and/or stronger solution.

LIMITATIONS

- ▶ Heavy grout haze or grout haze older than 10 days may require the use of **OxiTreat HD™**
- ▶ Use **MicroScrub™** to remove grout haze from polished natural stone & acid sensitive surfaces.

COVERAGE

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use
- ▶ Store between 4°C and 32°C.
- ▶ Do not re-use container. Discard in rubbish
- ▶ Clean tools with water.

FIRST AID

Contact Poisons Information Centre (Australia Ph:131126, NZ Ph:0800 764-766) or a doctor. **Ingestion:** Do not induce vomiting. Give water or milk to drink. **Eyes:** Immediately flush eyes with clean, running water for at least 15 minutes, & see a doctor. **Skin & Hair:** Remove contaminated clothing. Immediately wash contaminated skin & hair with plenty of water. **Inhalation:** Remove victim from exposure, to fresh air. Seek medical advice. **General:** If irritation persists or feeling unwell, seek medical attention.

| Code | Size | Barcode Number |
|---------|-------------------|----------------|
| 127-005 | 1ltr - Haze Away | 9347177001364 |
| 127-006 | 4 ltr - Haze Away | 9347177001371 |

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**