

# POLISH PRO

## Polishing Compound for Marble, Limestone, Travertine



**DESCRIPTION:** **POLISH PRO** is a highly effective, professional grade stone polishing compound to restore, re-polish & maintain worn polished calcium based stone e.g.: marble, limestone, travertine and cement based terrazzo. It will remove light etch marks, surface scratches, traffic wear patterns & produce an even glossy reflective finish. For calcium based stone e.g.: marble, limestone, travertine, cement based terrazzo where a smooth polished finish is desired.

**SURFACE USE:** For calcium based stone e.g.: marble, limestone, travertine and cement based terrazzo where a smooth polished finish is desired.

**TEST FIRST:** Always test first in an inconspicuous area to determine ease of application, dilution rate, colour stability and desired results. End user must determine suitability of product for their own use.

**PRECAUTIONS & SAFETY DIRECTIONS:**

1. Read entire label, SDS & product technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C and 32°C.
4. Do not allow product to come in contact with any non-recommended surfaces;
5. Surface must be clean and free of all surface sealers and coatings;
6. Mix well before using as product can settle.

**EQUIPMENT REQUIRED:**

1. Hogs hair or tan pads;
2. Weighted slow speed floor machine (175-300 RPM);
3. Clean water, wet vac, squeegee and broom;
4. **POLISH PRO**

**HOW TO USE:**

1. Sweep, vacuum, or wipe surface;
2. Slightly pre wet a small with 1-2 cups of clean water;
3. Add 2-3 tablespoons of **POLISH PRO** to the wet floor;
4. Use a weighted slow speed floor machine (175-300 RPM) with 2 x hogs hair or tan pads double stacked and then start the polishing process;
5. **DO NOT ALLOW PRODUCT TO DRY - ADD WATER OR POWDER TO THE SLURRY AS REQUIRED;**
6. Continue until the desired effect has been achieved;
7. Note: Use a squeegee to check your progress;
8. Remove the slurry with a wet vac and rinse thoroughly with clean water;
9. Repeat process as necessary;
10. Seal the surface with the appropriate Aqua-Seal STS™ sealer to provide stain resistance and ease the ongoing maintenance.

**LIMITATIONS:**

- Not suitable for black or green marble or granite, ceramic or porcelain tiles;
- Natural stone that is in highly damaged or worn condition will require restoration by diamond grinding.

**STAIN RESISTANCE & ONGOING MAINTENANCE**

After re-polishing surface, seal the area with a suitable sealer in order to provide stain resistance and ease the ongoing maintenance.

- **AQUA-SEAL GOLD+** for a natural look and premium stain protection;
- **ENHANCE'N'SEAL** for an colour enhanced look and premium stain protection;

**COVERAGE:**

Approx 30-40m<sup>2</sup> per 1kg. Coverage will vary depending on density, porosity, texture, surface absorption, weather, the application method, severity of the problem and dilution used.

**HANDLING, STORAGE & CLEAN UP:**

- Close container tightly after each use and keep upright;
- Store locked up in original container in a well ventilated cool area and protect from sunlight;
- Do not re-use container. Rinse and discard in rubbish;
- Clean tools and clothing with water before they dry;

**FIRST AID:**

Contact a doctor or Poisons Information Centre (Australia Ph: 131-126, NZ Ph: 0800 764766) or a doctor. If swallowed, do NOT induce vomiting. Immediately give at least 3-4 glasses of water. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information centre or a Doctor, or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, seek medical attention. In case of accident.

**SAFETY PRECAUTIONS:**

- Avoid contact with skin & eyes.
- Do NOT breath in fumes.

**HOW TO USE QUICK GUIDE:**

**Quick Guide for Polishing Stone with Polish Pro™**

To remove light scratches, etch marks, traffic wear patterns and create an even glossy reflective finish.

Note: Read entire label, technical bulletin and SDS before using. Always do a test area first.



Step 1 Surface must be clean and free of all surface sealers and coatings

Step 2 Pre-wet a small area with water & add 2-3 spoons of Polish Pro™ to form a slurry.

Step 3 Use a weighted slow speed scrubbing machine with hogs hair pad or tan pad.

Step 4 Remove some slurry and check on progress of the polished finish.

Step 5 When desired finish is achieved, then remove all slurry with wet vac and rinse thoroughly.

Step 6 An even, polished finish has been produced. Then seal with an Aqua-Seal sealer.

**MADE IN AUSTRALIA**

**PRODUCT WARRANTY - SEALERS PLUS** (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**



**SEALERS PLUS** (A DIVISION OF AQUA SEAL STS)

P: +61 2 9521 4000 - Mon - Fri 9.00am-4.00pm

E: sales@sealersplus.com.au www.sealersplus.com.au

