Poultice Plus

Ready to Use Stain Remover for Natural Stone, Terrazzo & Concrete

+ Heavy Duty Stain Remover – Pre-Mixed Paste
+ Helps Remove Oil, Food, Grease & Grime
+ Also Coffee, Tea & Red Wine Stains
+ Non-Flammable, Ready to Use – Just Apply & Cover
+ For Natural Stone, Terrazzo, Concrete, Tile & Grout

Product page, SDS & more

DESCRIPTION

Poultice Plus is a non-flammable, easy to use, pre-mixed **Professional Grade** poultice paste. It draws stains out of porous surfaces as it dries.

WHAT DOES IT DO

Helps remove most stains from oil, grease, food, coffee, tea, red wine and grime from natural stone, tile, concrete and grout.

SUITABLE FOR

All natural stone (including acid-sensitive marble, limestone and travertine), terrazzo, concrete, grout, porcelain, ceramic and encaustic tiles and other porous hard surfaces.

Surfaces

+ All Natural Stone
+ Marble & Limestone
+ Travertine & Granite
+ Terrazzo
+ Concrete
+ Grout
+ Porcelain & Ceramic
+ Encaustic Tiles

Stains

+ Cooking Oil & Grease
+ Food Stains
+ Coffee & Tea
+ Red Wine
+ Hydraulic & Motor Oil
+ Cosmetics & Creams
+ Grime
+ Indoor & Outdoor

WHERE TO USE

Indoor and outdoor, domestic and commercial: kitchens, benchtops, splashbacks, driveways, garages, patios and restaurants.

TEST FIRST

Due to the nature of different surfaces, do several test areas in inconspicuous areas to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

WHAT YOU NEED BEFORE YOU START

- Gloves and eye protection;
- Plastic spatula or putty knife to apply and remove;
- Foil or plastic wrap and glue residue free tape;
- Clean water and cloths for rinsing.

HOW TO USE

Ready to use. Surface must be clean, completely dry and free from sealers and coatings.

1. Stir well before using as product may settle (mix to a creamy toothpaste consistency; add a little water if needed);
2. Sweep, vacuum or wipe the surface;
3. Apply **Poultice Plus** about **6 mm thick** in a uniform coat over the stained area, covering an area slightly larger than the stain (ideally the whole stone or tile, to avoid a lighter patch);
4. Cover with foil or plastic wrap and tape down the borders with glue residue free tape;
5. Poke a few holes in the foil or plastic wrap;
6. Leave **Poultice Plus** covered until it dries – this may take 24 – 48 hours or longer, depending on conditions;
7. When dry, remove **Poultice Plus** from the surface with a plastic spatula;
8. Rinse thoroughly with clean water;
9. Repeat as necessary.

Note: for large or stubborn areas, use **Poultice Powder** mixed with water or the right liquid for the stain (see its Technical Bulletin), or use our Product Selector.

APPLICATION CONDITIONS

Use when the surface temperature is between 4°C and 32°C.

WATCH HOW TO USE

Watch: How to Remove Stains from Stone & Tile: Product Selector Guide
Not sure which product? Watch our stain removal guide
youtu.be/FJViGHKTTmc

SEALERS PLUS (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
Aust: sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026

Poultice Plus

Ready to Use Stain Remover for Natural Stone, Terrazzo & Concrete

PRECAUTIONS & SAFETY DIRECTIONS

1. Always test first;
2. Read entire label, SDS & technical bulletin before using;
3. Wear appropriate skin and eye protection;
4. Surface must be clean, completely dry and free from any sealers and coatings – remove them with **Strip-It** first;
5. Use when surface temperature is between 4°C & 32°C.

APPROXIMATE COVERAGE

Application	Thickness	Per 500 g Tub
Spot stain treatment	approx. 6 mm	**approx. 0.05 m²** (about 22 × 22 cm)

Coverage is **approximate only** and depends on the size and depth of the stain, the density, porosity and texture of the surface, weather conditions and the number of applications needed.

TECHNICAL DATA

Product type	Ready to use poultice (stain drawing) paste
Appearance	Grey paste, slight ammonia odour
pH	10 – 11
Application	Approx. 6 mm thick, covered, 24 – 48 h to dry
Application temp.	4°C – 32°C surface
Pack size	500 g tub (code 124-500)
Transport	Not a Dangerous Good
SDS	sealersplus.com.au/sds/Poultice-Plus-SDS.pdf

RELATED PRODUCTS – TAP TO VIEW

Poultice Powder	Stain remover powder for large areas	View ›
Active Plus	Oxygen cleaner & stain remover	View ›
Strip-It	Sealer & coating remover	View ›
Aqua-Seal Gold+	Premium natural look sealer	View ›

CAUTION

Not classified as hazardous according to Safe Work Australia (GHS 7). Not a Dangerous Good. Contains ethanolamine (<5%). Avoid contact with eyes and skin. Wear gloves and eye protection. Keep out of reach of children.

LIMITATIONS

- The degree of success depends on factors including the type of surface stained, the type of stain, how long it has been in place and whether the surface is sealed or unsealed;
- Some stains may be too deep to remove fully and may need more than one treatment;
- Will not remove etch marks or restore polish to damaged areas.

ONGOING MAINTENANCE

+ **Aqua-Seal Gold+** – seal once the stain is gone to help reduce future staining;
+ **EzyClean+** – pH neutral everyday cleaning of sealed surfaces.

HANDLING, STORAGE & CLEAN UP

- Close container tightly after each use. Store in the original container only;
- Store and use in temperatures between 4°C and 32°C;
- Wash hands, tools and clothes with clean water before product dries.

FIRST AID

For advice, contact Poisons Centre (Australia Ph: 131 126, NZ Ph: 0800 764 766) or a doctor. **Ingestion:** Rinse mouth. Do NOT induce vomiting. Give a glass of water. **Eyes:** Hold eyelids apart and flush continuously with running water for at least 15 minutes. **Skin & hair:** Remove contaminated clothing and flush with running water. **General:** If irritation persists, seek medical attention.

MADE IN AUSTRALIA

PRODUCT WARRANTY – SEALERS PLUS (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**

SEALERS PLUS (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
Aust: sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026