Spray'N'Seal (For Small Areas)

Aim, Spray & Seal – Premium Natural Look Aerosol Sealer

+ Natural Look, No Sheen – Breathable Penetrating Aerosol Sealer
+ Deep Stain & Water Resistance – Oil, Grease, Food & Grime
+ NanoPlus™ + RapidPlus™ Formula – Fast Drying
+ Clear, Non-Yellowing & UV Resistant – No Mixing, No Tools
+ Ideal for Grout Lines, Small Areas & Touch-Ups – 450 mL Can

Product page, SDS & more

DESCRIPTION

Spray'N'Seal is an easy to use, premium, natural look, breathable, penetrating aerosol sealer. The NanoPlus™ and RapidPlus™ formula gives quick drying plus deep stain and water resistance. Non-coating, non-yellowing and UV resistant. Just aim, spray and seal – ideal for grout lines, small areas, touch-ups and pre-sealing before grouting.

WHAT DOES IT DO

The fine sealing molecules penetrate below the surface and line the pores, reducing porosity without forming a film. Spills sit on the surface so they can be wiped up before they stain. By helping reduce water absorption it also helps reduce the conditions that can lead to efflorescence, mould and mildew.

SUITABLE FOR

All porous natural stone (marble, limestone, travertine etc), encaustic, terrazzo and porcelain tiles, mosaics, grout, bricks, Saltillo, terracotta, concrete and pavers. Also raw, untreated timber* and canvas (*test first). **Not for** glazed or non-porous surfaces, or surfaces with an existing sealer or coating.

Surfaces

+ Marble, Limestone & Travertine
+ Granite & Bluestone
+ Encaustic & Terrazzo
+ Porous Porcelain & Mosaics
+ Grout
+ Brick, Saltillo & Terracotta
+ Concrete & Pavers
+ Raw Timber* & Canvas

Where

+ Grout Lines
+ Floors & Walls
+ Bathrooms & Kitchens
+ Splashbacks
+ Touch-Ups & Repairs
+ Pre-Sealing Before Grouting
+ Indoor & Outdoor

WHERE TO USE

Indoor and outdoor, domestic and commercial areas. Use in a well ventilated area.

TEST FIRST

Always test first in an inconspicuous area to check ease of application, coats needed, colour and the final look. The end user must determine suitability of the product for their own use.

WHAT YOU NEED BEFORE YOU START

- Protective gloves and eye protection; a suitable mask if ventilation is limited;
- **XtremeClean+** or **Stone Wash+** to clean and prepare the surface;
- Plenty of paper towels or clean, absorbent cotton cloths to wipe off overspray.

PREPARATION

Surface must be clean, dry and free from other sealers and coatings. Use **XtremeClean+** or **Stone Wash+** as per label, rinse and allow to dry completely.

HOW TO USE – SEALING

1. Shake the can well before using;
2. Spray in an even, slow, sweeping motion directly onto the clean, dry surface from approx. 30 – 40 cm;
3. If overspray occurs, immediately wipe the surface **COMPLETELY DRY** with paper towels to remove the excess. Do NOT allow excess to dry on the surface;
4. Porous surfaces need more coats – allow 30 minutes between coats.

WATCH HOW TO USE

Watch: Spray'N'Seal Demonstration
Scan to watch Spray'N'Seal in action
youtu.be/yd-OTqlxsfc

HOW TO USE – PRE-SEALING

1. Pre-seal before installing, or 24 hours after installation. Do NOT saturate open grout joints;
2. Allow minimum 24 hours cure before grouting;
3. Dark or contrasting grout: apply **Grout Release+** after **Spray'N'Seal** has cured, then grout.

DRYING & CURING (20°C)

Between coats	**30 minutes**
Water test	**2 hours after final coat**
Light foot traffic	**After 2 hours**
Keep dry / cure	**24 – 48 hours**

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS and technical bulletin before using;
2. Wear appropriate gloves, skin and eye protection;
3. Use in a well ventilated area or wear a suitable mask. Do NOT spray on a naked flame or any ignition source. No smoking;
4. Use when surface temperature is between 4°C and 28°C;
5. Surface must be clean, dry and free from other sealers and coatings;
6. Do NOT use on the underside of the tile or stone. For six-sided / dip sealing use **Ultra-Block** or **Condense Plus**.

© October 2026

Spray'N'Seal (For Small Areas)

Aim, Spray & Seal – Premium Natural Look Aerosol Sealer

THE WATER DROP TEST

2 hours after the final coat, sprinkle a few drops of water. If it soaks in easily, apply another coat, wait 2 hours and test again. If the water no longer soaks in quickly and the surface does not darken, it is sealed.

APPROXIMATE COVERAGE (PER COAT)

Surface	Linear m / m² per 450 mL Can	Note
Grout joints	Up to 750 linear metres	**depends on joint width & depth**
Low porosity tile (e.g. porous porcelain)	Up to 10 m²	**per coat**
Porous stone, brick, concrete	Less than 10 m²	**more porous = lower coverage**

Coverage is **approximate only** and per coat. It depends on the density, porosity, texture and absorption of the surface, grout joint size, the weather, the application method and the number of coats. For larger areas use **Aqua-Seal Gold+**.

TECHNICAL DATA

Product type	Solvent-based penetrating aerosol sealer (short-chain C6 fluorinated acrylic copolymer)
Finish	Natural look, no sheen
Appearance	Clear, colourless liquid
Propellant	Hydrocarbon. Contains heptane and isopropanol
Application	4°C – 28°C; 30 min between coats
Pack size	450 mL aerosol can
Transport	Dangerous Good: UN1950 Aerosols, Class 2.1
SDS	sealersplus.com.au/sds/Spray-N-Seal-SDS.pdf

FIRST AID

Contact a doctor or Poisons Information Centre (Australia Ph: 131 126, NZ Ph: 0800 764 766). **Swallowed:** Rinse mouth. Do NOT induce vomiting. **Eyes:** Gently blot and flush with clean running water; if irritation persists, get medical advice. **Skin:** Remove contaminated clothing; wash thoroughly with warm water and soap. **Inhaled:** Remove to fresh air and rest. If unwell, seek medical attention.

ABOUT OUR FLUOROPOLYMER TECHNOLOGY

Modern short-chain C6 fluoropolymer; does not contain PFOS, PFOA or PFHxS (the long-chain substances restricted under IChEMS).

DANGER

Extremely flammable aerosol. Pressurised container: may burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects. Keep out of reach of children.

H222 H229 H304 H315 H336 H410. Keep away from heat, sparks and open flames; do not pierce or burn, even after use; avoid breathing spray; use only outdoors or in a well-ventilated area; wear gloves and eye protection. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

LIMITATIONS

- A penetrating sealer, not a membrane: it will NOT prevent surface wear, scuff marks or etching from harsh or acidic chemicals. Not a substitute for a compliant damp-proof membrane, drainage or correct substrate preparation;
- Wipe up spills immediately to help minimise staining;
- Best for small areas, grout lines and touch-ups – for floors and larger areas use **Aqua-Seal Gold+**.

EXPECTED WEAR & MAINTENANCE

Wear depends on traffic and the frequency and type of cleaning. Pressure washing, high alkaline, acidic or solvent cleaners and weather exposure all shorten life span; high traffic and exterior areas need more frequent re-application. Do the water drop test regularly and **re-seal as necessary**.

+ **EzyClean+** – everyday / weekly cleaning & disinfecting;
+ **Stone Wash+** – monthly / quarterly cleaning & conditioning;
+ **XtremeClean+** – periodic heavy duty cleaning.

HANDLING, STORAGE & CLEAN UP

- PRESSURISED DISPENSER. Protect from sunlight; do not expose to temperatures exceeding 50°C;
- Do not pierce or burn, even when empty. Store in a cool, well-ventilated place;
- Do not re-use the empty can. Dispose of empty cans in rubbish or recycle where accepted.

RELATED PRODUCTS – TAP TO VIEW

Aqua-Seal Gold+	Natural look sealer for larger areas	View ›
Grout Release+	Pre-grouting release coat	View ›
EzyClean+	Everyday cleaning & disinfecting	View ›
XtremeClean+	Heavy duty cleaning before sealing	View ›

MADE IN AUSTRALIA

PRODUCT WARRANTY – SEALERS PLUS (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**

© October 2026