Strip-It

Heavy Duty Sealer, Coating, Graffiti & Epoxy Grout Haze Remover

+ Removes Most Sealers, Coatings, Epoxy Grout Haze & Graffiti
+ Stays Wet Longer to Break Down Tough Residues
+ Ready to Use – Do NOT Dilute
+ Indoor, Outdoor, Domestic, Commercial & Industrial

Product page, SDS & more

DESCRIPTION

Strip-It is a **Professional Grade**, heavy duty, multi-purpose sealer and coating remover. Formulated to stay wet for longer periods to give the product time to break down and help remove tough residues.

WHAT DOES IT DO

Helps remove most sealers, coatings, epoxy grout haze, urethanes, synthetic finishes, adhesives, silicone, paint, ink, marker, deep-set oil stains and heavy wax and grease build-up.

+ Most sealers & coatings
+ Epoxy grout haze
+ Urethanes & synthetic finishes
+ Adhesives & silicone
+ Paint, ink, marker & graffiti
+ Deep-set oil stains
+ Heavy wax & grease build-up

SUITABLE FOR

Surfaces

+ Porcelain & Ceramic
+ Encaustic & Tessellated
+ Terrazzo & Mosaics
+ Grout & Concrete
+ Bricks & Pavers
+ Terracotta & Saltillo
+ Quarry Tiles
+ Engineered Stone

Natural Stone

+ Basalt & Bluestone
+ Granite & Quartz
+ Marble & Limestone
+ Sandstone & Slate
+ Travertine
+ All Natural Stone

WHERE TO USE

Indoor, outdoor, domestic, commercial and industrial areas.

TEST FIRST

Always test first in an inconspicuous area to determine ease of application, dwell time, colour stability and desired results. User must determine suitability for their use.

WHAT YOU NEED BEFORE YOU START

- Chemical resistant gloves, eye protection and a suitable mask;
- Plastic container, roller, mop, brush or sponge to apply;
- White nylon pad, scrub brush or slow speed scrubber;
- Wet vac or mop and plenty of clean water for rinsing.

HOW TO USE

1. Do NOT dilute. Use neat. Pour into a suitable container;
2. Using a roller, mop, brush or sponge, carefully apply a liberal amount of **Strip-It** to a manageable area;
3. Allow a minimum dwell time of 30 minutes – up to 2 hours depending on the problem (the longer the better);
4. **DON'T ALLOW PRODUCT TO DRY ON SURFACE – ADD MORE PRODUCT TO KEEP WET AND ACTIVE**;
5. Scrub with a white nylon pad, scrub brush or scrub machine (slow speed scrubber for large areas);
6. Remove the dirty solution with a wet vac or mop;
7. Rinse thoroughly with clean water;
8. Repeat the process as necessary.

NOTE: To help with residue removal, apply **XtremeClean+** diluted 1:5 with water after step 7, scrub again, then rinse thoroughly.

CONDITIONS & DRYING

1. Use when surface temperature is between 4°C & 32°C;
2. Surface ready for light traffic after 1 hour or after all fumes and vapours have dissipated;
3. Allow at least 48 hours drying time before applying any sealers, coatings or floor finishes. Always do a test area before applying a new sealer or coating to the whole area.

WATCH HOW TO USE

Watch: Removing / Stripping Old Coatings & Sealers – Strip-It
Scan to watch the Strip-It how-to video
youtu.be/E5fKPwRnJJA

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin and eye protection – causes serious eye damage;
3. Do NOT breathe in fumes or vapours – wear an appropriate mask. Use in a well ventilated area;
4. Avoid contact during pregnancy or while nursing;
5. Do NOT allow contact with painted or waxed surfaces. Will affect sealers, coatings, floor finishes, deck stains & painted surfaces;
6. Do NOT mix with other chemicals;
7. Floor will get slippery during the process. Take appropriate precautions to prevent slips and falls;
8. **WASH UNDERSIDE OF SHOES BEFORE STEPPING ONTO OTHER AREAS.**

SEALERS PLUS (An Aqua-Seal Brand) – Technical Support
P: +61 2 9521 4000 Monday to Friday 9.00am – 4.00pm E: support@sealersplus.com.au
U5, 5 Clerke Place, Kurnell NSW 2231 Australia
Aust: sealersplus.com.au **NZ:** sealersplus.co.nz **Global:** sealersplus.com

© October 2026

Strip-It

Heavy Duty Sealer, Coating, Graffiti & Epoxy Grout Haze Remover

APPROXIMATE COVERAGE

Application (neat)	m² per Litre	m² per 4 L Bottle
Single coat sealer / light coating	30 – 40	**120 – 160**
Average job	20 – 30	**80 – 120**
Thick or multiple coatings, epoxy haze, graffiti	10 – 20	**40 – 80**

Coverage is **approximate only** (approx. 10 – 40 m² per litre) and depends on the type and severity of the problem, porosity of the surface, dwell time and weather conditions.

TECHNICAL DATA

Product type	Ready to use, solvent-based sealer & coating remover
Appearance	Colourless to yellowish liquid, characteristic odour
Dilution	None – use neat
Dwell time	30 minutes – 2 hours, keep wet
Re-seal	After at least 48 hours drying
Shelf life	Approx. 3 years unopened – less after opening
Pack sizes	1 Litre · 4 Litre
Transport	Not a Dangerous Good
SDS	sealersplus.com.au/sds/Strip-It-SDS.pdf

LIMITATIONS

- Removal of thick or multiple coatings may require multiple applications of **Strip-It**;
- For lighter sealers, coatings and epoxy haze try water-based **Aqua-Strip**;
- For stains, see the Stain Removal Guide in our **Product Selector**.

HANDLING, STORAGE & CLEAN UP

- Close container tightly after each use and keep upright. Store locked up in the original container in a well ventilated cool area, protected from sunlight;
- Shelf life approx. 3 years unopened – less after opening. Storage beyond that time does not necessarily mean the product is not usable – do a test area first;
- Do not re-use container. Rinse and discard in rubbish. Wash tools, gloves and shoes with water before they dry.

DANGER

Hazardous according to Safe Work Australia (GHS 7). Not a Dangerous Good. **H302** Harmful if swallowed. **H315** Causes skin irritation. **H318** Causes serious eye damage. Avoid breathing fumes, mists, vapours or spray. Wear protective gloves, clothing and eye or face protection. Do not eat, drink or smoke when using. Keep out of reach of children.

FIRST AID

Immediately contact Poisons Centre (Australia Ph: 131 126, NZ Ph: 0800 764 766) or a doctor. **Ingestion:** Rinse mouth. Do NOT induce vomiting. **Eyes:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **Clothes:** Remove contaminated clothing and wash before re-use. **Skin & hair:** Wash with plenty of soap and water. **Inhalation:** Move to fresh air and keep at rest. **General:** If any irritation persists get medical advice.

AFTER STRIPPING – RE-SEAL

+ **Aqua-Seal Gold+** – premium penetrating sealer;
+ **Gloss'N'Seal** – gloss coating sealer;
+ **EzyClean+** – routine pH neutral cleaning.

MADE IN AUSTRALIA

PRODUCT WARRANTY – SEALERS PLUS (A Division of Aqua-Seal STS™) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.**