HOW TO APPLY GRIP-IT T

Step-by-step instructions for porcelain, ceramic and tessellated tiles

sealersplus

Treat, test, then rinse

Grip-It T creates a fine micro-texture on the tile surface to help make slippery tiles safer underfoot. You control the result: test as you go, and once you're happy with the achieved result, pick it up and rinse it off.

- Ready to use. Do not dilute
- Test every 5 minutes until you're happy with the achieved result
- Pick up with a wet vac, then rinse multiple times with clean water
- Not a sealer or a coating. Won't peel
- A long-lasting slip-resistant treatment
- For porcelain, ceramic and tessellated tiles only
- Not for any non-recommended surfaces

GRIP-IT T
1 LITRE

GRIP-IT T
4 LITRE

SUITABLE FOR

- Porcelain tiles
- Ceramic tiles
- Tessellated tiles
- Floors, indoors and outdoors

WHERE TO USE

- **Domestic:** homes, units, duplexes etc
- **Commercial:** hotels, shopping centres, airports, supermarkets, bars etc
- **Industrial:** workshops, factories etc

NOT FOR

- Natural stone, terrazzo or quarry tiles
- Glass, metal, chrome or coated surfaces

WHAT YOU'LL NEED

- Grip-It T
- Chemical-resistant gloves, eye protection and protective footwear
- Stopwatch or phone timer
- Flat mop or applicator, stiff broom, 2 buckets
- Wet vac (recommended) or squeegee and mop
- Plenty of clean water
- Masking tape and plastic
- XtremeClean+ for the pre-clean

BEFORE YOU START

- Always do a test area first
- Surface temperature must not be below 4°C or above 28°C
- Out of direct sun and wind; underfloor heating off
- Tiles clean and dry
- Keep children and pets away until the floor is rinsed and dry
- Use tools kept only for this job

IMPORTANT NOTE

Read entire Product Label, SDS and Technical Bulletin before using any product. ALWAYS TEST A SMALL AREA to determine the ease of application & desired results. Anti-slip results vary with the tile, its glaze and the number of applications. Anti-slip treatments help reduce slip risk; they are not a substitute for correct falls and drainage or regular cleaning.

STEP-BY-STEP



Prepare the floor

Clean the tiles with XtremeClean+, rinse well and let dry. Mask stainless steel, chrome, glass, natural stone and drains. Turn off underfloor heating and work out of direct sun. Surface temperature must not be below 4°C or above 28°C.



Do a test area first

VERY IMPORTANT

Run the full process (steps 3–9) on a spare tile or hidden spot. Check for colour stability and any surface change when fully dry. Note how many applications gave the grip you want.

Apply Grip-It T

Wear gloves, eye, skin and foot protection. Pour into a plastic tray or bucket (**never straight from the bottle onto the tiles**) and apply with a sponge, roller or mop so a wet film sits evenly over the tiles. Don't spray. Work in sections you can keep wet and control.



Start your stopwatch

Start timing as soon as the section is evenly wet. Add more product to keep it wet and active. **You always want a wet film of Grip-It T on the surface.**



Test after 5 minutes

Wipe a small spot with a damp cloth.
Finger test: with a gloved finger, rub firmly back and forth across the spot. It should feel grippy and drag, not smooth and glassy.
Shoe test: in a rubber-soled shoe, put your weight on the spot and do a skid/scuff or twisting motion on the tiles. Compare both with an untreated tile.



Need more grip? Repeat

Apply a fresh coat over the **whole section** and test again after another 5 minutes. Repeat until you're happy with the achieved result.



Never let it dry

Never let it dry: add more product to the surface to keep it wet and active. You always want a wet film of Grip-It T on the surface. This may take a few applications, depending on how hard the glaze is and how much grip you want. Not happy after 3 applications? Rinse and contact us.



Pick it up straight away

Once you're happy with the achieved result, remove Grip-It T straight away so it stops working. We recommend a wet vac. No wet vac? Squeegee and bucket, or use a mop and bucket kept for this job and wring it out often.

Rinse multiple times

Rinse multiple times with plenty of clean water and pick up each rinse. Don't let the floor dry between rinses. No wet vac? Rinse at least 3 times with fresh water each time.



Check the result when dry

Check the grip both dry and wet. Dispose of the waste water as your local council requires, never into stormwater drains or the garden.

TIPS FOR THE BEST RESULT

- Work in sections you can keep wet and control, and top up over the whole section, not just the dry patches
- On dark tiles, check the test area when fully dry
- Have the wet vac and rinse water ready before you start, so you can pick up Grip-It T as soon as you're happy with the achieved result
- Never let Grip-It T dry: add more product to the surface to keep it wet and active. You always want a wet film of Grip-It T on the surface

AFTERCARE

EzyClean+: **Daily / Weekly** cleaning, pH neutral.

XtremeClean+: **Half yearly or as needed** heavy-duty clean.

Aqua-Seal Gold+: seal the grout joints after 24 hours to help reduce staining (optional).

PRECAUTIONS

- Read the label, SDS and Technical Bulletin before use
- Wear chemical-resistant gloves, eye, skin and foot protection; ventilate well
- Don't mix Grip-It T with any other product
- Obtain calcium gluconate gel before starting, in case product gets on skin
- Protect surrounding surfaces, metal surfaces, fixtures and plants
- **WASH UNDERSIDE OF SHOES BEFORE STEPPING ONTO OTHER AREAS.**